

# AIR TANK



## »» SPECIFICATIONS

Carbon steel and low alloy steel gas tank (0.8 ~ 1.6 MPa)															
No.	Specification Capacity(m <sup>3</sup> ) Pressure(Mpa)	Designed temperat ure °C	Height H	Diameter	Air inlet			Air outlet			Support		Safety value nozzle	Drain value nozzle	Matched Air Compressor Capacity (m <sup>3</sup> /min)
					H1	DN	Thread	H2	DN	Thread	D	d			
1	0.3/0.8	110	1586	550	645	50	Rp1 1/2	1235	50	Rp11/2	400	20	Rp3/4	R1/2	2.5~3
2	0.3/1.0														
3	0.3/1.3														
5	0.5/0.8	110	2086	600	630	50	Rp1 1/2	1630	50	Rp11/2	420	20	Rp3/4	R1/2	4~5
6	0.5/1.0														
7	0.5/1.3														
5	0.6/0.8	110	2116	650	645	65	Rp1 1/2	1645	65	Rp11/2	420	20	Rp3/4	R1/2	4.8~5
6	0.6/1.0														
7	0.6/1.3														
9	1.0/0.8	110	2200	800	690	65	Rp1 1/2	1820	65	Rp11/2	560	24	Rp1	R1/2	8~10
10	1.0/1.0														
10	1.0/1.3														
13	1.5/0.8	110	2289	1000	680	65	Rp2	1930	65	Rp2	700	24	Rp1	R1/2	12~15
14	1.5/1.0														
15	1.5/1.3														
17	2.0/0.8	110	2789	1000	780	80	Rp2	2280	80	Rp2	700	24	Rp1/4	R1/2	16~20
18	2.0/1.0														
19	2.0/1.3														
21	2.5/0.8	110	2740	1200	880	80		2200	80		840	24	Rp1 1/4	R1/2	20~25
22	2.5/1.0														
23	2.5/1.3														
25	3.0/0.8	110	2940	1200	880	80		2280	80		840	24	Rp11/2	R3/4	24~30
26	3.0/1.0														
27	3.0/1.3														
29	4.0/0.8	110	3050	1400	930	100		2430	100		1050	24	Rp11/2	R3/4	32~40
30	4.0/1.0														
31	4.0/1.3														
33	5.0/0.8	110	3630	1400	930	100		2990	100		1050	24	Rp2	R3/4	40~50
34	5.0/1.0														
35	5.0/1.3														

Specifications are subject to change without notice.